



Ex p Systems Configuration sheet

company	Contact person
adress - place	street
phone No.	mobile phone
fax No.	e-mail

Inquiry number	Quantity	Delivery in week	
Supplied Documentation	Circuit diagram	Bill of materials	Data Sheets

place of installation

Zone 1 (2G) ATEX	Zone 2 (3G) ATEX	Ambiet temperature	to	°C
Zone 21 (2D) ATEX	Zone 22 (3D) ATEX			

execution

Stainlees steel V2A (1.4301, AISI 304)	Plinth, Height (mm)
Stainlees steel V4A (1.4401, AISI 316L)	saltwater-resistant
Painted sheet steel (RAL 7035 grey)	Lifting eye
Paintwork RAL	lock with key
Window viewing size (mm) Width	Height

Operating data

AC 230 V (L/N/PE)	24 V DC	Current consumption	A
AC 400 V (3L/N/PE)	Other	Internal power dissipation	Watt

Power release

Direct activation
(By Ex p control / max. 5 A, 2 contacts)

Indirecte activation
(By additional Ex-proof power relay)

Activation outside hazardous area

Flushing medium

cleaned compressed air
Inert gas

External Cable glands, control and Signal devices

Cable glands see attachment
Built-in appliances see attachment

Form download: <http://www.exepd.de/ex-p-steuerschraenke-1.html>
Fill out the form, print it and fax it. To 09343-62 70 55 99 or
Save your form and send it by e-mail via 2Attach to e-mail".

Exepd GmbH
i_Park Tauberfranken 23
D-97922 Lauda-Königshofen

Phone +49 (0) 9343 627055-0
Fax +49 (0) 9343 627055-99
www.exepd.de