

company	contact person
adress - place	street
phone No.	mobile phone
fax No.	e-mail

inquiry number	quantity	Unit	delivery in KW
supplied documentation	circuit diagram	bill of materials	data sheets

plase of installation

Zone 1 (2G) ATEX	Zone 2 (3G) ATEX	ambient temperature	to	°C
Zone 21 (2D) ATEX	Zone 22 (3D) ATEX			

Material / Housing

Polyester (black, RAL 9005)	stainlees steel V2A (1.4301, AISI 304)		
Aluminium (grey, RAL 7001)	stainlees steel V4A (1.4404, AISI 316L)		
Painted sheet steel (grey, RAL 7035)			
size (mm)	width	height	depth

Installations Interior / Exterior

digital display (1)	type	pc	supplied	
panel (2)	type	pc	suppleid	
push butten (3)	pc	function	pc	function
double push- button (4)	pc	function	pc	function
selector 0-1 (5) latching-latching	pc	function	pc	function
selector 0-1 (6) latching-momentary	pc	function	pc	function
selector 1-0-2 (7) latching-latching-latching	pc	function	pc	function
selector 1-0-2 (8) momentary-latching-momentary	pc	function	pc	function
emergency stop push button (9)	pc	function		
illuminated push button (10)	pc	function	pc	function
illuminated push button (11)	pc	function	pc	function
illuminated push button (12)	pc	function	pc	function
indicator lights (13)	color	pc	pc	pc
		pc	pc	pc
potentiometer (14)		pc	pc	pc
blind plugs (15)		pc		

terminals size

(piece)

unit wired

unit unwired

earth plate

earth bolt M8

marking (tag label)

cable glands side A

size pc type

size pc type

size pc type

size pc type


cable glands side C

size pc type

size pc type

size pc type

size pc type



cable glands side D

size pc type

size pc type

size pc type

size pc type

cable glands side B

size pc type

size pc type

size pc type

size pc type

*) Please add your preferred arrangement of the control and signal devices to this sketch by using the numbers 1 - 15.

additional text